

## **Features**

Rated current: up to 28A Rated voltage:up to 630V

Signal: 12 Pins, 17 Pins

Power: 5+PE

Protection Degree: IP67

Assembly and panel type Installation

Suitable for standard connection technology

## Advantages

- □ Perfect compatibility with each brand.
- □ A variety of combinations meet multiple installation environments.
- $\hfill = 360\ensuremath{\,^\circ}$  EMC shielding, suitable for complex electromagnetic environments.
- □ Optimize the structure. Improve the wire ends locking to reduce trouble risks; Innovative anti-return contact pins to prevent the internal structure from loosening; Second locking system improve product reliability.
- ☐ Anti-vibration ensure high reliability in harsh environment.
- □ Easy installation, even non-professionals can quickly complete the assembly and replace the defective parts.
- □ Complete test report.

## **Applications**







Encoder Servo motor Robot



## M23 series products

Product	Description	contact front view	Rated current /voltage	Withstand voltage ( AC/1Min)	Insulation resistance	Diameter	Temperature	Protection Degree
PCSH-M23P-06P-FF-SL7001-00A(H)	M23 Assembly Female plug Crimping Shielding Pin: 5+PE		28A/630V	4.0 KV	≥100MΩ	12~14AWG	-40°C∼+125°C	IP67
PCSH-M23P-06P-MM-SL7001-00A(H)	M23 Assembly Male socket Crimping Shielding Pin: 5+PE	9 1 1 4 9 9 9 2 PE 9 2						
SCSH-M23P-06P-MM-SF7001-00A(H)	M23 Panel Type Male socket Crimping Shielding Pin: 5+PE	65 0 1 4 0 0						
PCSH-M23R-12P-FF-SL7001-00A(H)	M23 Assembly Female plug Crimping Shielding Pin: 12	0 <sup>1</sup> 0 <sup>9</sup> 0 0 <sup>2</sup> 10 <sup>1</sup> 12 <sup>8</sup> 0 0 <sup>3</sup> 0 <sup>1</sup> 0 <sup>7</sup> 0 0 <sup>4</sup> 0 <sup>5</sup> 0	8A/160V	2.5 KV	≥100MΩ	18~24AWG	-40°C~+125°C	IP67
PCSH-M23R-12P-MM-SL7001-00A(H)	M23 Assembly Male socket Crimping Shielding Pin: 12	8 12 10 2 8 12 10 3 7 11 3 6 5 4						
SCSH-M23R-12P-MM-SS7000-00A(H)	M23 Panel Type Male socket Crimping Shielding Pin: 12	8 12 10 2 8 12 10 2 7 11 3 6 5 4						
PCSH-M23R-17P-FF-SL7001-00A(H)	M23 Assembly Female plug Crimping Shielding Pin: 17	0101100 02130169 03140158 001705	8A/125V	2.0 KV	≥100MΩ	18~24AWG	-40°C∼+125°C	IP67
PCSH-M23R-17P-MM-SL7001-00A(H)	M23 Assembly Male socket Crimping Shielding Pin: 17	9 16 0 13 2 8 15 0 14 3 7 0 17 0 1						
SCSH-M23R-17P-MM-SS7000-00A(H)	M23 Panel Type Male socket Crimping Shielding Pin: 17	110 12 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1						

Tel: +86-574-63504333 E-mail: sale@degson.com www.degson.com

Fax: +86-574-63512345